

**LOCTITE 495** 

## **Safety Data Sheet**

Page 1 of 9

SDS No.: 427632

V001.8

Revision: 15.03.2016 printing date: 18.07.2017

#### Section 1. Identification of the substance/preparation and of the company/undertaking

**LOCTITE 495 Product name:** 

LOCTITE 495 BO20G PL/RU/EE/UA Other means of identification:

Product code: IDH246580

Recommended use of the chemical and restrictions on use

**Intended use:** Adhesive

Identification of manufacturer, importer or distributor

Importer: Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia. Phone

:+ 603 22461000 Fax: + 60322461188

E-mail address of person

responsible for Safety Data **Sheet:** 

ap-ua-psra.sea@henkel.com

**Emergency information:** 

FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call

CHEMTREC: +1 703-741-5970

## Section 2. Hazards identification

### **GHS Classification:**

**Hazard Class Hazard Category** Target organ

Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Specific target organ toxicity -

single exposure

respiratory tract irritation Category 3

### **GHS** label elements:

Hazard pictogram:



Signal word:

Warning

SDS No.: 427632 Page 2 of 9

V001.8 LOCTITE 495

**Hazard statement:** H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

**Precaution:** 

**Prevention:** P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P280 Wear eye protection/face protection.

P280 Wear protective gloves.

**Response:** P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340+P311 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or doctor/ physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Disposal:** P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

## Section 3. Composition / information on ingredients

### **Substance or Mixture:**

Mixture

### Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Ethyl 2-cyanoacrylate	60- 100 %	Skin corrosion/irritation 2
7085-85-0		H315
		Serious eye damage/eye irritation 2
		H319
		Specific target organ toxicity - single exposure 3
		H335
Hydroquinone	< 0.1 %	Acute toxicity 4; Oral
123-31-9		H302
		Serious eye damage/eye irritation 1
		H318
		Skin sensitizer 1
		H317
		Germ cell mutagenicity 2
		H341
		Carcinogenicity 2
		H351
		Acute hazards to the aquatic environment 1
		H400
		Chronic hazards to the aquatic environment 1
		H410

SDS No.: 427632 Page 3 of 9

V001.8 LOCTITE 495

### Section 4. First aid measures

**Inhalation:** Move to fresh air, consult doctor if complaint persists.

Skin contact: Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a

spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate

enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin. If lips are accidentally stuck together apply warm water to the lips and encourage

maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact: If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help

to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of

cyanoacrylate trapped behind the eyelid cause any abrasive damage.

**Ingestion:** Ensure that breathing passages are not obstructed. The product will polymerise

immediately in the mouth making it almost impossible to swallow. Saliva will slowly

separate the solidified product from the mouth (several hours).

Indication of immediate medical attention and special treatment

needed:

See section: Description of first aid measures

### Section 5. Fire fighting measures

**Suitable extinguishing media:** Foam, extinguishing powder, carbon dioxide.

Fine water spray

Specific hazards arising from the

chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides

(NOx) can be released.

Special protection equipment and

precautions for firefighters:

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

### Section 6. Accidental release measures

**Personal precautions:** Ensure adequate ventilation.

**Environmental precautions:** Do not let product enter drains.

**Clean-up methods:** Do not use cloths for mopping up. Flood with water to complete polymerization and

scrape off the floor. Cured material can be disposed of as non-hazardous waste.

## Section 7. Handling and storage

Handling: Ventilation (low level) is recommended when using large volumes

Use of dispensing equipment is recommended to minimise the risk of skin or eye contact

**Storage:** For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C

(35.6 - 46.4 °F)

SDS No.: 427632 Page 4 of 9

V001.8 LOCTITE 495

## Section 8. Exposure controls / personal protection

#### Components with specific control parameters for workplace:

ETHYL CYANOACRYLATE 7085-85-0	Value type	Time Weighted Average (TWA):
	ppm	0.2
	Remarks	ACGIH
ETHYL CYANOACRYLATE 7085-85-0	Value type	Time Weighted Average (TWA):
	ppm	0.2
	Remarks	MY OEL
HYDROQUINONE 123-31-9	Value type	Time Weighted Average (TWA):
	mg/m <sup>3</sup>	1
	Remarks	ACGIH
HYDROQUINONE 123-31-9	Value type	Time Weighted Average (TWA):
	mg/m <sup>3</sup>	2
	Remarks	MY OEL

**Respiratory protection:** Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if

the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:** Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection

index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq$  0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6,

corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the

gloves should be replaced.

**Eye protection:** Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk

of splashing.

Protective eye equipment should conform to EN166.

**Body protection:** Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for

dusts.

**Engineering controls:** Ensure good ventilation/extraction.

**Hygienic measures:** Wash hands before work breaks and after finishing work. Do not eat, drink or smoke while

working. Good industrial hygiene practices should be observed.

### Section 9. Physical and chemical properties

Appearance: colourless to yellowish

liquid

Odor: No data available.
Odor threshold (CA): No data available.

V001.8 LOCTITE 495

pH: No data available.

Melting point / freezing point: No data available.

Specific gravity: No data available.

Boiling point: > 149 °C (> 300.2 °F)

Flash point: 80 - 93 °C (176 - 199.4 °F)

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapor pressure:

No data available.

No data available.

Vapor pressure:

No data available.

(no method; 50 °C (122 °F))

Vapor density:No data available.Density:No data available.Solubility:No data available.Partition coefficient: n-No data available.

octanol/water:

Auto ignition:No data available.Decomposition temperature:No data available.Viscosity:No data available.

**VOC content:** < 3 %

(2010/75/EC)

## Section 10. Stability and reactivity

Reactivity/Incompatible

materials:

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and

alcohols.

Chemical stability: Stable under recommended storage conditions.

Conditions to avoid: Stable under normal conditions of storage and use.

Hazardous decomposition

products:

None if used for intended purpose.

## Section 11. Toxicological information

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

## Acute oral toxicity:

Ethyl 2-cyanoacrylate	Value type	LD50	
7085-85-0	Value	> 5,000 mg/kg	
	Species	rat	
	Method	OECD Guideline 401 (Acute Oral Toxicity)	
Hydroquinone	Value type	LD50	
Hydroquinone 123-31-9	Value type Value	LD50 367 mg/kg	

Page 6 of 9 SDS No.: 427632 **LOCTITE 495** 

V001.8

## Acute dermal toxicity:

Ethyl 2-cyanoacrylate	Value type	LD50
7085-85-0	Value	> 2,000 mg/kg
	Species	rabbit
	Method	OECD Guideline 402 (Acute Dermal Toxicity)

## Skin corrosion/irritation:

Ethyl 2-cyanoacrylate	Result	slightly irritating
7085-85-0	Exposure time	24 h
	Species	rabbit
	Method	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

## Serious eye damage/irritation:

Ethyl 2-cyanoacrylate	Result	irritating
7085-85-0	Exposure time	72 h
	Species	rabbit
	Method	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

## Respiratory or skin sensitization:

Ethyl 2-cyanoacrylate	Result	not sensitising
7085-85-0	Test type	
	Species	guinea pig
	Method	
Hydroquinone	Result	sensitising
123-31-9	Test type	Guinea pig maximisation test
	Species	guinea pig
	Method	

# Germ cell mutagenicity:

Ethyl 2-cyanoacrylate	Result	negative
7085-85-0	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Ethyl 2-cyanoacrylate	Result	negative
7085-85-0	Type of study / Route of administration	mammalian cell gene mutation assay
	Metabolic activation / Exposure time	with and without
	Method	OECD Guideline 476 (In vitro Mammalian Cell Gene
		Mutation Test)
Ethyl 2-cyanoacrylate	Result	negative
Ethyl 2-cyanoacrylate 7085-85-0	Result Type of study / Route of administration	in vitro mammalian chromosome aberration test
		8
	Type of study / Route of administration	in vitro mammalian chromosome aberration test
	Type of study / Route of administration Metabolic activation / Exposure time	in vitro mammalian chromosome aberration test with and without
7085-85-0 Hydroquinone	Type of study / Route of administration Metabolic activation / Exposure time	in vitro mammalian chromosome aberration test with and without OECD Guideline 473 (In vitro Mammalian Chromosome
7085-85-0	Type of study / Route of administration Metabolic activation / Exposure time Method	in vitro mammalian chromosome aberration test with and without OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
7085-85-0  Hydroquinone	Type of study / Route of administration Metabolic activation / Exposure time Method  Result	in vitro mammalian chromosome aberration test with and without OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) negative

## Repeated dose toxicity:

Hydroquinone	Result	NOAEL=>= 250 mg/kg
123-31-9	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 days5 days/week. 12 doses
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral
		Toxicity in Rodents)
Hydroquinone	Result	LOAEL=<= 500 mg/kg
123-31-9	Route of application	oral: gavage
	Exposure time / Frequency of treatment	14 days5 days/week. 12 doses
	Species	rat
	Method	OECD Guideline 407 (Repeated Dose 28-Day Oral
		Toxicity in Rodents)

SDS No.: 427632 Page 7 of 9

V001.8 LOCTITE 495

## Section 12. Ecological information

General ecological information: Biological and Chemical Oxygen Demands (BOD and COD) are insignificant.

**Ecotoxicity:** Do not empty into drains / surface water / ground water.

### **Toxicity:**

Hydroquinone	Value type	LC50
123-31-9	Value	0.638 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Hydroquinone	Value type	EC50
123-31-9	Value	0.134 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydroquinone	Value type	EC50
123-31-9	Value	0.335 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Selenastrum capricornutum (new name: Pseudokirchnerella subcapitata)
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroquinone	Value type	EC 50
123-31-9	Value	0.038 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	

## Persistence and degradability:

Ethyl 2-cyanoacrylate	Result	
7085-85-0	Route of application	aerobic
	Degradability	57 %
	Method	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroquinone	Result	readily biodegradable
123-31-9	Route of application	aerobic
	Degradability	75 - 81 %
	Method	EU Method C.4-E (Determination of the "Ready" BiodegradabilityClosed
		Bottle Test)

## Bioaccumulative potential / Mobility in soil:

Ethyl 2-cyanoacrylate	LogKow	0.776
7085-85-0	Temperature	22 °C
	Method	EU Method A.8 (Partition Coefficient)
Hydroquinone	LogKow	0.59
123-31-9	Temperature	
	Method	EU Method A.8 (Partition Coefficient)

## Section 13. Disposal considerations

### **Product**

Method of disposal: Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorised

landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

SDS No.: 427632 Page 8 of 9

V001.8 LOCTITE 495

which it is used

### **Packaging**

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

### Section 14. Transport information

### Road transport ADR:

Not dangerous goods

### Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Not dangerous goods

#### **Marine transport IMDG:**

Not dangerous goods

### Air transport IATA:

Class: 9
Packing group: III
Packaging instructions (passenger): 964
Packaging instructions (cargo): 964
UN no.: 3334
Label: 9

Proper shipping name: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)

Additional Information: Primary packs containing less than 500ml are unregulated by this

mode of transport and may be shipped unrestricted.

### Section 15. Regulatory information

Regulatory Information: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous

Chemicals) Regulations 2013 [P.U.(A) 310/213]

Industry Code of Practice on Chemicals Classification and Hazard Communication

#### Global inventory status:

Regulatory list Notification

TSCA yes
NDSL yes
IECSC yes
ISHL (JP) yes

## Section 16. Other information

**Disclaimer:** This information is based on our current level of knowledge and relates to the product in

the state in which it is delivered. It is intended to describe our products from the point of

view of safety requirements and is not intended to guarantee any particular properties.

SDS No.: 427632 Page 9 of 9

V001.8 LOCTITE 495