

Safety Data Sheet

Page 1 of 10

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

SDS No.: 153461

V003.3

Revision: 02.05.2018 printing date: 05.07.2018

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS

TRABAJO PESADO

Other means of identification: LOCTITE 271 6ML EN,ES

Product code: IDH487232

Recommended use of the chemical and restrictions on use

Intended use: Adhesive

Identification of manufacturer, importer or distributor

Importer: Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia.

Phone :+ 603 22461000 Fax : + 60322461188

E-mail address of person responsible for Safety Data

Sheet:

ap-ua-psra.sea@henkel.com

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call

CHEMTREC: +1 703-741-5970

Section 2. Hazards identification

GHS Classification:

<u>Hazard Class</u> <u>Hazard Category</u> <u>Target organ</u>

Serious eye damage/eye irritation Specific target organ toxicity -

single exposure

Category 2
Category 3 respiratory tract irritation

GHS label elements:

Hazard pictogram:

Signal word: Warning

Page 2 of 10

SDS No.: 153461 V003.3

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Hazard statement: H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precaution:

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product characteristics at time of

disposal.

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Section 3. Composition / information on ingredients

Substance or Mixture:

Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Cumene hydroperoxide	1- 10 %	Organic peroxides E
80-15-9		H242
		Acute toxicity 4; Oral
		H302
		Acute toxicity 3; Inhalation
		H331
		Acute toxicity 4; Dermal
		H312
		Skin corrosion/irritation 1B
		H314
		Specific target organ toxicity - repeated exposure 2 H373
		Chronic hazards to the aquatic environment 2 H411
N,N-Diethyl-p-toluidine	0.1- 1 %	Acute toxicity 3; Oral
613-48-9		H301
		Acute toxicity 3; Inhalation
		H331
		Acute toxicity 3; Dermal
		H311
		Specific target organ toxicity - repeated exposure 2 H373
		Chronic hazards to the aquatic environment 3 H412
N,N-dimethyl-o-toluidine	0.1- 1 %	Acute toxicity 3; Oral
609-72-3	0.1- 1 70	H301
009-72-3		Acute toxicity 3; Inhalation
		H331
		Acute toxicity 3; Dermal
		H311
		Specific target organ toxicity - repeated exposure 2 H373
		Chronic hazards to the aquatic environment 3 H412
Methyl methacrylate	0.1- 1 %	Flammable liquids 2
80-62-6	0.1 1 /0	H225
		Skin corrosion/irritation 2
		H315
		Skin sensitizer 1
		H317
		Specific target organ toxicity - single exposure 3
		H335

Section 4. First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention

from a specialist.

Page 4 of 10

SDS No.: 153461

V003.3

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Indication of immediate medical attention and special treatment needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media: Foam, extinguishing powder, carbon dioxide.

Specific hazards arising from the

chemical:

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides

(NOx) can be released.

Additional fire fighting advice: Cool endangered containers with water spray jet.

Section 6. Accidental release measures

Personal precautions: Ensure adequate ventilation.

Environmental precautions: Do not let product enter drains.

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Handling: Use only in well-ventilated areas.

Gloves and safety glasses should be worn

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Page 5 of 10

SDS No.: 153461 V003.3

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

METHYL METHACRYLATE 80-62-6	Value type	Time Weighted Average (TWA):
	ppm	50
	Remarks	ACGIH
METHYL METHACRYLATE 80-62-6	Value type	Time Weighted Average (TWA):
	ppm	100
	mg/m ³	410
	Remarks	MY OEL
METHYL METHACRYLATE 80-62-6	Value type	Short Term Exposure Limit (STEL):
	ppm	100
	Remarks	ACGIH

Respiratory protection: Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if

the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or

splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural

rubber (NR; >=1 mm thickness) Suitable materials for longer, direct contact

(recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the

gloves should be replaced.

Eye protection: Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk

of splashing.

Protective eye equipment should conform to EN166.

Body protection: Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for

dusts.

Engineering controls: Ensure good ventilation/extraction.

Hygienic measures: Good industrial hygiene practices should be observed. Wash hands before work breaks

and after finishing work. Do not eat, drink or smoke while working.

Section 9. Physical and chemical properties

Appearance: red liquid
Odor: mild

Odor threshold (CA): No data available.

pH: Not available.

Page 6 of 10

SDS No.: 153461 V003.3

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Melting point / freezing point: No data available.

Specific gravity: 1.1

Boiling point: > 149 °C (> 300.2 °F) **Flash point:** > 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

Evaporation rate: No data available.
Flammability (solid, gas): No data available.
Lower explosive limit: No data available.
Upper explosive limit: No data available.
Vapor pressure: < 6.5 mbar

(; 27 °C (80.6 °F))

Vapor density:No data available.Density:1.1 g/cm3Solubility:No data available.Partition coefficient: n-
octanol/water:No data available.

Auto ignition:No data available.Decomposition temperature:No data available.Viscosity:No data available.

VOC content: < 3 %

(2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible Acids.

materials: Strong oxidizing agents.

Reducing agents.

Chemical stability: Stable under recommended storage conditions.

Conditions to avoid: No decomposition if used according to specifications.

Hazardous decomposition Oxides of carbon. Oxides of nitrogen.

Section 11. Toxicological information

Oral toxicity: Acute toxicity estimate (ATE): > 2,000 mg/kg

Method: Calculation method

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l

Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method

Acute toxicity estimate (ATE): > 20 mg/l

Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method

Dermal toxicity: Acute toxicity estimate (ATE) : > 2,000 mg/kg

Method: Calculation method

Acute toxicity estimate (ATE): > 2,000 mg/kg

Method: Calculation method

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Symptoms of Overexposure: EYE: Irritation, conjunctivitis.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Acute oral toxicity:

Cumene hydroperoxide	Value type	LD50
80-15-9	Value	550 mg/kg
	Species	rat
	Method	not specified

Acute dermal toxicity:

Cumene hydroperoxide	Value type	LD50
80-15-9	Value	1,200 - 1,520 mg/kg
	Species	
	Method	not specified

Skin corrosion/irritation:

Cumene hydroperoxide	Result	corrosive
80-15-9	Exposure time	
	Species	rabbit
	Method	Draize Test

Respiratory or skin sensitization:

Methyl methacrylate	Result	sensitising
80-62-6	Test type	Mouse local lymphnode assay (LLNA)
	Species	mouse
	Method	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

Cumene hydroperoxide	Result	positive
80-15-9	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide	Result	negative
80-15-9	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified
Methyl methacrylate	Result	negative
80-62-6	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	with and without
	Method	not specified

Repeated dose toxicity:

Cumene hydroperoxide	Result	
80-15-9	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified
Methyl methacrylate	Result	LOAEL=2000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study
Methyl methacrylate	Result	NOAEL=1000 ppm
80-62-6	Route of application	inhalation
	Exposure time / Frequency of treatment	14 weeks6 hrs/day, 5 days/wk
	Species	mouse
	Method	Dose Range Finding Study

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Section 12. Ecological information

Ecotoxicity:

Do not empty into drains / surface water / ground water.

Toxicity:

Cumene hydroperoxide	Value type	LC50
80-15-9	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide	Value type	EC 50
80-15-9	Value	7 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	24 h
	Species	Water flea (Daphnia magna)
	Method	, ,
	Value type	EC50
	Value	18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide	Value type	ErC50
80-15-9	Value	3.1 mg/l
20 10 7	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide	Value type	EC10
80-15-9	Value	70 mg/l
00 13 7	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	50 mm
	Method	not specified
N,N-dimethyl-o-toluidine	Value type	LC 50
609-72-3	Value	46 mg/l
009-72-3	Acute Toxicity Study	Fish
		96 h
	Exposure time Species	
	Method	Fathead minnow (Pimephales promelas)
Mathadan athan and at		LC50
Methyl methacrylate 80-62-6	Value type	
80-02-0	Value	350 mg/l
	Acute Toxicity Study	Fish
	Exposure time	7 ' '1
	Species	Leuciscus idus
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Methyl methacrylate	Value type	EC50
80-62-6	Value	69 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Methyl methacrylate	Value type	EC50
80-62-6	Value	170 mg/l
	Acute Toxicity Study	Algae
	Exposure time	4 d
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
	Value type	NOEC
	Value	100 mg/l
	Acute Toxicity Study	Algae
	Exposure time	4 d
	Species	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
M-4111-4-	Value type	EC0
Methyl methacrylate	Value	100 mg/l

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Acute Toxicity Study	Bacteria
Exposure time	30 min
Species	
Method	not specified

Persistence and degradability:

Cumene hydroperoxide	Result	
80-15-9	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Methyl methacrylate	Result	readily biodegradable
80-62-6	Route of application	aerobic
	Degradability	95 %
	Method	EU Method C.4-B (Determination of the "Ready" BiodegradabilityModified
		OECD Screening Test)

Bioaccumulative potential / Mobility in soil:

Cumene hydroperoxide	Bioconcentration factor (BCF)	9.1
80-15-9	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide	LogPow	2.16
80-15-9	Temperature	
	Method	not specified
Methyl methacrylate	LogPow	1.38
80-62-6	Temperature	
	Method	not specified

Section 13. Disposal considerations

Product

Method of disposal: Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Packaging

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Not dangerous goods

Marine transport IMDG:

Not dangerous goods

Page 10 of 10

SDS No.: 153461 V003.3

LOCTITE® HEAVY-DUTY THREADLOCKER 271 FIJADOR DE ROSCAS TRABAJO PESADO

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

Regulatory Information: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous

Chemicals) Regulations 2013 [P.U.(A) 310/213]

Industry Code of Practice on Chemicals Classification and Hazard Communication

Global inventory status:

Regulatory list	Notification
TSCA	yes
NDSL	yes
ENCS (JP)	yes
KECI (KR)	yes
PICCS (PH)	yes
IECSC	yes
ISHL (JP)	ves

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.