

Safety Data Sheet

LOCTITE 573

Page 1 of 7

SDS No.: 153496

V001.9

Revision: 22.08.2017 printing date: 05.07.2018

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 573

Other means of identification: LOCTITE 573 TTL250MLCZ/HU/PL/RU

Product code: IDH246621

Recommended use of the chemical and restrictions on use

Intended use: Anaerobic Adhesive

Identification of manufacturer, importer or distributor

Importer: Henkel Malaysia Sdn Bhd 46th Floor, Menara TM, Jalan Pantai Baharu, 59200 Kuala Lumpur, Malaysia. Phone

:+ 603 22461000 Fax : + 60322461188

E-mail address of person

responsible for Safety Data

Sheet:

Emergency information: FOR EMERGENCIES ONLY (Spill, major leak, Fire, Exposure, or Accident). Call

CHEMTREC: +1 703-741-5970

ap-ua-psra.sea@henkel.com

Section 2. Hazards identification

GHS Classification:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

GHS label elements:

Substance or mixture is not classified as hazardous according to Globally Harmonized System(GHS).

SDS No.: 153496 Page 2 of 7

V001.9 LOCTITE 573

Section 3. Composition / information on ingredients

Substance or Mixture:

Mixture

Declaration of hazardous chemical:

Hazard component CAS-No.	Content	GHS Classification
Cumene hydroperoxide	0.1- 1 %	Organic peroxides E
80-15-9		H242
		Acute toxicity 4; Oral
		H302
		Acute toxicity 3; Inhalation
		H331
		Acute toxicity 4; Dermal
		H312
		Skin corrosion/irritation 1B
		H314
		Specific target organ toxicity - repeated exposure 2
		Н373
		Chronic hazards to the aquatic environment 2
		H411

Section 4. First aid measures

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap.

Seek medical advice.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary

Ingestion: Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

Indication of immediate medical attention and special treatment

needed:

See section: Description of first aid measures

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Special protection equipment and precautions for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Sulphur oxides

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

Ensure adequate ventilation. See advice in section 8

Environmental precautions: Do not let product enter drains.

SDS No.: 153496 Page 3 of 7

V001.9 LOCTITE 573

Clean-up methods: For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Handling: Use only in well-ventilated areas.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Avoid skin and eye contact. See advice in section 8

Storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Respiratory protection: Use only in well-ventilated areas.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if

the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection: Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection

index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6,

corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the

gloves should be replaced.

Eye protection: Wear protective glasses.

Protective eye equipment should conform to EN166.

Body protection: Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for

dusts.

Engineering controls: Ensure good ventilation/extraction.

Hygienic measures: Good industrial hygiene practices should be observed. Wash hands before work breaks

and after finishing work. Do not eat, drink or smoke while working.

V001.9 LOCTITE 573

Appearance: green paste

Odor: characteristic
Odor threshold (CA): No data available.
pH: 3.00 - 6.00
Melting point / freezing point: No data available.

Specific gravity: 1.25

Boiling point: > 150.0 °C (> 302 °F) **Flash point:** > 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

Evaporation rate:

Flammability (solid, gas):

Lower explosive limit:

Upper explosive limit:

Vapor pressure:

(no method; 50 °C (122 °F))

No data available.

No data available.

Vo.27 mbar

< 300 mbar

Vapor density:No data available.Density:1.0800 g/cm3Solubility:No data available.Partition coefficient: n-No data available.

octanol/water:

Auto ignition:No data available.Decomposition temperature:No data available.Viscosity:No data available.

VOC content: < 3.00 %

(2010/75/EC)

Section 10. Stability and reactivity

Reactivity/Incompatible Reaction with strong acids. **materials:** Reacts with strong oxidants.

Chemical stability: Stable under recommended storage conditions.

Conditions to avoid: Stable

Conditions to avoid: Hazardous decomposition

products:

carbon oxides. Sulphur oxides nitrogen oxides

Irritating organic vapours.

Section 11. Toxicological information

Inhalative toxicity: Acute toxicity estimate (ATE) : > 20 mg/l

Exposure time: 4 h Test atmosphere: Vapor. Method: Calculation method

Symptoms of Overexposure: Prolonged or repeated contact may cause skin irritation.

Prolonged or repeated contact may cause eye irritation.

Acute oral toxicity:

Cumene hydroperoxide	Value type	LD50
80-15-9	Value	550 mg/kg
	Species	rat
	Method	not specified

SDS No.: 153496 Page 5 of 7 LOCTITE 573

V001.9

Acute dermal toxicity:

Cumene hydroperoxide	Value type	LD50
80-15-9	Value	1,200 - 1,520 mg/kg
	Species	
	Method	not specified

Skin corrosion/irritation:

Cumene hydroperoxide	Result	corrosive
80-15-9	Exposure time	
	Species	rabbit
	Method	Draize Test

Germ cell mutagenicity:

Cumene hydroperoxide	Result	positive
80-15-9	Type of study / Route of administration	bacterial reverse mutation assay (e.g Ames test)
	Metabolic activation / Exposure time	without
	Method	OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide	Result	negative
80-15-9	Type of study / Route of administration	dermal
	Metabolic activation / Exposure time	
	Species	mouse
	Method	not specified

Repeated dose toxicity:

Cumene hydroperoxide	Result	
80-15-9	Route of application	inhalation: aerosol
	Exposure time / Frequency of treatment	6 h/d5 d/w
	Species	rat
	Method	not specified

Section 12. Ecological information

General ecological information: Cured Loctite products are typical polymers and do not pose any immediate

environmental hazards.

Do not empty into drains / surface water / ground water. **Ecotoxicity:**

Toxicity:

Cumene hydroperoxide 80-15-9	Value type	LC50
	Value	3.9 mg/l
	Acute Toxicity Study	Fish
	Exposure time	96 h
	Species	Oncorhynchus mykiss
	Method	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide	Value type	EC50
80-15-9	Value	18 mg/l
	Acute Toxicity Study	Daphnia
	Exposure time	48 h
	Species	Daphnia magna
	Method	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide	Value type	ErC50
80-15-9	Value	3.1 mg/l
	Acute Toxicity Study	Algae
	Exposure time	72 h
	Species	Pseudokirchneriella subcapitata
	Method	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide	Value type	EC10
80-15-9	Value	70 mg/l
	Acute Toxicity Study	Bacteria
	Exposure time	30 min
	Species	
	Method	not specified

SDS No.: 153496 Page 6 of 7

V001.9 LOCTITE 573

Persistence and degradability:

Cumene hydroperoxide	Result	
80-15-9	Route of application	no data
	Degradability	0 %
	Method	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Cumene hydroperoxide	Bioconcentration factor (BCF)	9.1
80-15-9	Exposure time	
	Species	calculation
	Temperature	
	Method	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
Cumene hydroperoxide	LogPow	2.16
80-15-9	Temperature	
	Method	not specified

Section 13. Disposal considerations

Product

Method of disposal: Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in

which it is used

Packaging

Disposal of uncleaned packages: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Section 14. Transport information

General information:

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

Section 15. Regulatory information

Regulatory Information: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous

Chemicals) Regulations 2013 [P.U.(A) 310/213]

Industry Code of Practice on Chemicals Classification and Hazard Communication

Global inventory status:

Regulatory list Notification

TSCA yes
NDSL yes
KECI (KR) yes
IECSC yes

SDS No.: 153496 Page 7 of 7

V001.9 LOCTITE 573

Section 16. Other information

Disclaimer:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.